

	<p>CS Series 2 - 15 W 0.01 Ω - 82k Ω E 24 Standard - Tol. = 3%</p>	<p>SR Series Lade- und Entladewiderstände Résistances pour condensateur 10 & 13 W 0.1 Ω - 68 k Ω E 24 Standard - Tol. = 3%</p>	
	<p>RB Series 10 - 250 W 0.01 Ω - 120 k Ω E 24 Standard - Tol. = 3%</p>	<p>RB / 6 Series Verlängerte Kriechstrecke Ligne de fuite prolongé 25 & 50 W 0.1 Ω - 68 k Ω E 24 Standard - Tol. = 3%</p>	
	<p>RB / 7 Series 6,3 mm Flachstecker - Anschlüsse Connexion pour languette Faston 6.3 mm 25 & 50 W 0,1 Ω - 68 k Ω E 24 Standard Tol. = 3%</p>	<p>RB / 8 Series M4 -Schraubanschlüsse Connexion par vis M4 50 W 0.1 Ω - 68 k Ω E 24 Standard To. = 3%</p>	
	<p>RB 106 - RB 256 Series Verlängerte Kriechstrecke Ligne de fuite prolongé 150 & 250 W 0.1 Ω - 120 k Ω E 24 Standard Tol. = 3%</p>	<p>3 SM Series SMD Widerstände Résistances CMS 3W 0.1 Ω - 10 k Ω E 12 Tol. 5% - 1%</p>	
	<p>PR 250 Series Dickfilmwiderstände Résistances couche épaisse 250 W 1 Ω - 1 M Ω E 12 Tol. 10% - 1%</p>	<p>PR 254 Series Dickfilmwiderstände Résistances couche épaisse 250 W 1 Ω - 1 M Ω E 12 Tol. 10% - 1%</p>	